



**STANDARD APPLICATION**  
**FOOT MOUNTED MOTOR**  
**WOUND ROTOR**

TYPE - A000  
 STYLE - WBO / WBS / WBT

Unit Shown in Assembly Position A101 - F1

\* Auxiliary Terminal Box is Available  
 Upon Customer Request.

RUNOUT TOLERANCE  
 SHAFT .003

NEMA STANDARD TAPERED SHAFT  
 1-1/4" Taper Per Foot  
 Locknut & Washer Furnished

FEET TO SHAFT CENTERLINE  
 TOLERANCE +.000 - .031

Frame	B	C	D	E	F	L	M	N	U	V	W
444 TX	18.00	40.81	11.00	9.00	7.25	20.56	14.50	5.75	3.375	5.25	.25
445 TX	20.00	42.81			8.25	21.56	15.50		3.374		

Frame	AE	BA	FC	FN	FV	FW	FY	XN	◆ XV	XW	XZ
444 TX	11.00	7.50	47.69	6.88	4.12	1.00	1.75	6.12	5.62	.25	6.69
445 TX			49.69								

REULAND ELECTRIC CO.



Industry, Calif.

Howell, Mich.

replaces  
 NONE

DRAWN *JV*  
 APPR. *JV*

◆ Revised  
 ● Added  
 REV. A  
 1/15/85

dwg no  
 RDA21-0009-A